



Simple. Natural. Hardwoods®



ALDER

Scientific Name: Alnus Rubra

Red Alder, native to the Pacific Northwest, has a uniform honey color with limited differences between heartwood and sapwood. Coupled with its reliable stability, it is a popular choice for both furniture and cabinetry. With a closed grain and fine texture, the rich light brown color sets during the drying process (8.5% MC) that limits darkening and yellowing over time like other species are susceptible to.

This relatively soft hardwood is easy to work with, excelling in machining and fine finishing. It stains well and can be finished in a variety of shades and colors, offering a valuable alternative for a wide array of projects. Alder's availability in various grades allows for flexibility in design and applications- from rustic to refined contemporary pieces, aligning with the needs of both artisan craftsmen and large-scale manufacturers.

What's Alder Used For?

- Cabinetry
- Vanities
- Furniture
- Millwork
- Musical Instruments
- Moulding



Why Alder?

- Close grain, fine texture
- Uniform honey color
- Excellent finishing
- Easy to machine and process
- Strategic alternative to poplar, soft maple and more

Quick Fact

Alder serves as a stable-cost alternative to Poplar and Soft Maple, favored for its price reliability amidst the market volatility of other hardwoods.



Learn More




NWH Alder is available as PEFC certified, FSC Mix Credit, FSC Controlled Wood or PEFC Controlled Sources.



Simple. Natural. Hardwoods®

Alder



Weight per Bdft: 2.45
 Specific Gravity (Density): 0.41
 Hardness (Janka): 590
 Bending Strength (MOR): 9800
 Bending Stiffness (MOE): 1380
 Dimensional Movement (Shrinkage): R 4.4%, T 7.3%



Grades We Offer




Superior




Cabinet



CAB



Premium



Standard Frame

North American Hardwood Species Comparison Chart

| Lumber (12% Moisture Content) | Machining | Sanding | Finishing | Gluing | Fastening Nailing/ Screwing | Weight per bdf | Specific Gravity (Density) | Hardness (Janka) | Bending Strength (MOR) | Bending Stiffness (MOE) | Dimensional Movement (Shrinkage) | |
|----------------------------------|-----------|---------|-----------|--------|-----------------------------------|-------------------|----------------------------------|---------------------|------------------------------|-------------------------------|--|-------|
| | | | | | | | | | | | R (%) | T (%) |
| Alder | 10 | 10 | 10 | 9 | 7 | 2.45 | .41 | 590 | 9800 | 1380 | 4.4 | 7.3 |
| Ash | 9 | 10 | 9 | 8 | 6 | 3.56 | .61 | 1320 | 15000 | 1740 | 4.9 | 7.8 |
| Basswood | 10 | 10 | 9 | 8 | 8 | 2.50 | .37 | 410 | 8700 | 1460 | 6.6 | 9.3 |
| Cherry | 10 | 9 | 10 | 9 | 7 | 3.07 | .52 | 950 | 12300 | 1490 | 3.7 | 7.1 |
| Hickory | 3 | 7 | 7 | 3 | 3 | 4.14 | .67 | 1820 | 13700 | 1730 | 4.9 | 8.9 |
| Hard Maple | 9 | 8 | 10 | 9 | 4 | 3.73 | .64 | 1450 | 15800 | 1830 | 4.8 | 9.9 |
| PC Maple | 9 | 9 | 10 | 9 | 5 | 2.74 | .50 | 850 | 10700 | 1450 | 3.7 | 7.1 |
| Soft Maple | 8 | 9 | 10 | 9 | 5 | 3.19 | .55 | 950 | 13400 | 1640 | 4.0 | 8.2 |
| Red Oak (Northern) | 10 | 10 | 9 | 9 | 7 | 3.64 | .63 | 1220 | 14380 | 1761 | 4.0 | 8.6 |
| Oregon White Oak | 9 | 9 | 9 | 8 | 8 | 4.34 | 0.72 | 1640 | 10200 | 1090 | 4.2 | 9.0 |
| White Oak (Eastern) | 9 | 10 | 9 | 7 | 7 | 3.94 | .68 | 1350 | 14380 | 1762 | 4.4 | 8.8 |
| Poplar | 9 | 8 | 10 | 9 | 6 | 2.81 | .43 | 540 | 10100 | 1580 | 4.6 | 8.2 |
| Walnut | 9 | 8 | 9 | 7 | 7 | 3.36 | .56 | 1010 | 14600 | 1680 | 5.5 | 7.8 |
| Yellow Birch | 10 | 8 | 10 | 8 | 2 | 3.53 | .62 | 1260 | 16600 | 2010 | 7.3 | 9.5 |